


Data sheet

Part No.	UPRM Turbo BK UV
Description	rigid conduit, with sectional corrugation, with moulded-on coupler medium compression resistance, medium impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	33411
Compression resistance	> 750 N



Standard: EN 61386-1, EN 61386-21



Compressive strength	Impact strength	Operating temperature	Bending strength	UV resistant
Medium (class 3)	Medium (class 3)	-25 to +60°C	Rigid	true

Art. no.	AD	ID	VPE small/medium/large
108 511	16mm	13mm	3 m / 111 m / 6216 m
108 512	20mm	16,8mm	3 m / 111 m / 3996 m
108 513	25mm	21,4mm	3 m / 57 m / 2622 m
108 514	32mm	27,8mm	3 m / 57 m / 1368 m
108 515	40mm	35,4mm	3 m / 21 m / 966 m
108 516	50mm	44,3mm	3 m / 21 m / 630 m
108 517	63mm	56mm	3 m / 21 m / 378 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed)	True
Outdoor installation	True
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Details	
Halogen free	False
With sleeve	True
Fire retardant version	True
Material	PVC-U